

technical data sheet

PennWhite Ltd, Aston Way, Midpoint 18 Business Park, Middlewich, Cheshire, CW10 0HS

Description

FoamDoctor® F2960 is a powerful food-safe foam control agent based on an aqueous emulsion of vegetable oil, polyethers and non-ionic surfactants.

Applications

FoamDoctor® F2960 is suitable for use in a wide variety of food processing applications and is particularly useful in the processing of blood products.

Product Features

FoamDoctor® F2960 is formulated for use in applications which use membrane filtration in their downstream processes. It will inhibit foaming even when used at low doses made.

Method of Use

FoamDoctor® F2960 should be dosed by a suitable metering pump directly into the system immediately prior to the point where foaming occurs. Dosing rates should be optimised by trial but are typically 5 - 20 ppm.

Product Safety

A Safety Data Sheet compliant with EU 2015/830 is available for FoamDoctor® F2960 on request. It contains any safe handling guidelines that may be relevant to this product.

Storage, Shelf Life & Packaging

FoamDoctor® F2960 has a shelf life of 12 months when stored in original and unopened containers between 5°C and 30°C. Agitate well before use. This product is typically available in 25, 220 and 1,000 litre containers. Please note that it is sold in kilograms and the actual capacity of a container (in kg) is dependent upon the specific gravity of its contents.

Compliance

- US FDA CFR 21 173.340 (Defoaming Agents)
- EU Regulation (EC) 1333/2008 (Food Additives)
- EU Regulation (EU) 231/2012 (Specifications for food additives listed in Annexes I and II of (EC) 1333/2008)
- Kosher and Parev (Manchester Beth Din)
- Halal (Halal Food Authority, London)



Typical Properties

- Solids: 25.0 – 27.0 %
- Appearance: White emulsion
- Viscosity: 500 – 900 cP

Please note; these are typical properties only and should NOT be construed or used as a specification for this product.

(OPM3/D3)

TDS: 168

Issue: 08

Revised: 26/09/2019

Page 1 of 1



This product is manufactured in a facility whose Quality Management System is certified as being in conformity with ISO 9001:2015 by Intertek Certification Ltd.



This product is manufactured in a facility which operates in line with the Chemical Business Association's Responsible Care program.

Technical Support Contact Details

Telephone: +44 (0)1606 734820

Fax: +44 (0)1606 837867

Email: info@pennwhite.co.uk

Website: www.pennwhite.co.uk