

technical data sheet

PennWhite Ltd, Aston Way, Midpoint 18 Business Park, Middlewich, Cheshire, CW10 0HS

Description

Prodet X317 is a graphite heat-resistant lubricant.

Applications

Prodet X317 is formulated to remove excessive deposits of pigmented lubricants on commercial oven chains whilst re-lubricating the chains.

Product Features

Prodet X317 has a high penetration power and detergency action to remove deposits and provide effective lubrication in operating temperatures up to 600°C.

Method of Use

Prodet X317 should be applied to chains by brush, mop, oil can, low pressure spray or by automatic applicator. Oven temperature during application should be between 10°C and 180°C. Prodet X317 should be applied as required, typically once per month of operation. Prodet X317 may be used in conjunction with PennWhite's Cuperol HT lubricant.

Product Safety

A Safety Data Sheet compliant with EU 2015/830 is available for Prodet X317 on request. It contains any safe handling guidelines that may be relevant to this product.

Storage, Shelf Life & Packaging

Prodet X317 has a shelf life of 12 months when stored in original and unopened containers between 5°C and 30°C. It is available in 20kg packs.

Typical Properties

- Graphite Content: 7.0 – 9.0 %wt
- Specific Gravity: 0.910 – 0.920
- Stability: No precipitation
- Viscosity: 300 – 400 cP

Please note; these are typical properties only and should NOT be construed or used as a specification for this product.

(OPM3/D2)

TDS: 006

Issue: 08

Revised: 06/07/2021

Page 1 of 1



This product is manufactured in a facility whose Quality Management System is certified as being in conformity with ISO 9001:2015 by Intertek Certification Ltd.



This product is manufactured in a facility which operates in line with the Chemical Business Association's Responsible Care program.

Technical Support Contact Details

Telephone: +44 (0)1606 734820

Fax: +44 (0)1606 837867

Email: info@pennwhite.co.uk

Website: www.pennwhite.co.uk